

## DESCRIPTION

The Model DCS is a duress call station with a panic button, and a 3 kHz oscillator mounted to the back of a single gang stainless steel faceplate. Unit fits into a standard single gang electrical box (not supplied) for flush or surface mounting. When panic button is pressed, an audio signal activates the Louroe Base Station and identifies the zone. Compatible only with Louroe Models DG-12/25 series alarming base stations. Model DCS can be wired directly to the base station, or tied in with a Louroe Microphone or Speaker/Microphone for providing one-way listen or two-way talk/listen with the base station.



MODEL DCS

## APPLICATION

- Parking Structures
- Stairwells
- Elevator Lobbies
- Secured Walkways
- Elevator Cabs
- Detention Centers

### WIRING REQUIREMENTS

2 Conductor **shielded** cable, 22 gauge with a 24 gauge drain wire

**NOTE:** Unshielded cable is not satisfactory for audio systems

West Penn 452 or equivalent



## FEATURES

- Pushbutton activation
- May be tied in with a Louroe Microphone (or Speaker/Microphone) for communications with the Louroe Base Station
- Fits in a standard single gang electrical box for flush or surface mounting
- Interface with DG-12/25 series alarming base stations

## SPECIFICATIONS

▪ Tone output	3 Vrms into 10K $\Omega$ load @ 3 kHz
▪ Supply voltage	12 Vdc
▪ Dimensions	4 "L x 2 "W
▪ Weight	2.5 oz $\frac{3}{4}$
▪ Shipping Weight	1 lb

### IMPORTANT NOTICE

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.



Federal Law References:  
Federal Regulations, US Code, Title 18.  
Crime and Criminal Procedure, Sec 2510.

