LOUROE ELECTRONICS
6955 VALJEAN AVE, VAN NUYS,
PH: (818)994-6498 / FAX: (818)994-6458
techsupport@louroe.com / www.louroe.com

VeriFact®-650/665

Installation and Operating Instructions

VeriFact®-665
Ceiling Mount (6.5” speaker)

VeriFact®-665
Ceiling Mount (5.5” speaker)

DESCRIPTION

Louroe Model VeriFact-650 and VeriFact-665 are ceiling mount full range speaker-microphones with fire-domes designed to provide 2-way audio (listen/talkback) with various modes of audio/video transmission systems such as:

- DVR’s
- IP Network Cameras
- PC Soundcards
- Video Servers

The VeriFact-650/665 provide line level audio input and output. Both models have built in amplifiers that drive either a 5.5” speaker (VeriFact-650) or 6.5” speaker (VeriFact-665).

The gain of the microphone is factory adjusted. The gain of the audio output (speaker) can be adjusted using the potentiometer on the PCB on the rear of the unit, the adjustment should be done in small increments.

To adjust the audio output of the speaker, rotate the blue potentiometer clockwise (increase) or counterclockwise (decrease) slowly until the desired loudness is attained.

It is recommended to use the device in half duplex mode, however the unit has a built-in echo-cancellation system for when the device is configured for use in full duplex mode such that if the device recognizes that the audio output is beyond a set internal level, the incorporated microphone will be muted till the audio level falls.

The use of headphones or earphones is strongly recommended on the audio monitoring/receiving system to avoid acoustic feedback, this is essential on monitoring systems that do not have echo-cancellation functionality.

INTERCONNECTION DIAGRAM

**CONNECTING LOUROE™ MODEL VeriFact-650/665
DIRECTLY TO AN IP CAMERA, DVR,
VIDEO SERVER, ETC. USING 3-COND. SHIELDED CABLE**

5-PIN TERMINAL BLOCK IDENTIFIER OF VeriFact-650/665

(black)	PWR = 12VDC
(black w/stripe)	GND = Power Ground
(red)	OUT = Audio Output (microphone)
(bare)	GND = Ground (audio) and Ground (speaker) (black wire)
(white)	IN = Speaker in from external device



WIRING REQUIREMENTS

3 Conductor consisting of:
+ 2 Conductor **shielded**, 20 gauge with 22 gauge drain
+ 1 Conductor **unshielded**, 20 gauge

All in the same jacket

3.5mm STEREO CONNECTION



3.5mm MONO CONNECTION



RCA CONNECTION



Dimensions and Frequency response curve for VeriFact-665



Unit: mm



Dimensions and Frequency response curve for VeriFact-650



Unit: mm



Specifications and Mechanical Dimesions

SPECIFICATIONS (Microphone)

Type	Electret Condenser
Audio output	Line level (0 dB @ 600Ω) unbalanced
Microphone element sensitivity	-45 dB
Frequency response	40 Hz - 15 kHz
Audio Input Impedance	600

SPECIFICATIONS (Speaker VeriFact - 665)

Speaker power output	10W
Speaker impedance	2K Ohm
Speaker magnet	Neodymium
Speaker size	6.5”
Current Drain	1.0A
Supply Voltage	12 Vdc
Dimensions	9” Dia x 5” H
Weight	4 lbs
Shipping Weight	6 lbs

SPECIFICATIONS (Speaker VeriFact - 650)

Speaker power output	6W
Speaker impedance	2K Ohm
Speaker magnet	Neodymium
Speaker size	5.5”
Current Drain	700 mA
Supply Voltage	12 Vdc
Dimensions	7.2” Dia x 5” H
Weight	3 lbs
Shipping Weight	5 lbs

Listed product - this product must be installed with a listed LPS or Class 2 power supply.

MANUFACTURED IN THE

IMPORTANT NOTICE

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.

Federal Law References:
Federal Regulations, US Code, Title 18. Crime and Criminal Procedure, Sec 2510.

WARRANTY

LOUROE ELECTRONICS warrants that at the time of shipment products manufactured by LOUROE ELECTRONICS to be free of defects in material and workmanship.

Should a defect appear within five years (60 months) from date of shipment, LOUROE ELECTRONICS will, at its sole discretion, repair or replace the defective equipment. This equipment shall not be accepted for repair or return without prior notification by LOUROE ELECTRONICS .

This warranty does not extend to any Louroe product that has been subjected to improper or incorrect installation, misuse, accident, or in violation of installation instructions provided by LOUROE ELECTRONICS.

Returned shipments to LOUROE ELECTRONICS shall be at customer's expense. LOUROE ELECTRONICS will return the equipment prepaid via best way

LOUROE ELECTRONICS® 6955 VALJEAN AVENUE, VAN NUYS, CA 91406 TEL (818) 994-6498 FAX (818)994-6458
website: www.louroe.com e-mail: sales@louroe.com